


Trimless Adjustable LED Downlight

LED Downlight-COB 8W

Model No.: SL-XQ208008 01

Version: V1.0

Date: June15th,2020



Ø75-80

Features

- 355° Horizontally Rotatable, 0° ~ 30° Tilting Adjustable.
- Optical Flexibility 15/24/36 /50 Degree Beam Angle.
- Interchangeable Reflector In Various Finishing.
- Modular Design, Pre Build-In Frame, It Is Easy For Debugging And Maintenance.
- High Quality Aluminum Heat Sink With Excellent Thermal Dissipation.
- Ra90/95 High Color Rendering Is More Realistic, Restores The True Color Of The Subject.
- CCT Range 2700K/3000K/3500K/4000K/5000K/5500K
- Constant Current Driver Output With Flicker Free, Led Driver Efficiency 85-90%
- Supporting To Triac Dimming, 0/1-10V And Dali Dimming .
- 3 Years Warranty.

Application:

Widely Use In Commercial And Residential Lighting, Like Hotels, Villa, Culbs, Restaurants, Offices, Shops And Home, Etc

Luminaire Specification

| | |
|--------------------|-----------|
| Height | H 95mm |
| Bezel | Ø 110mm |
| Hole cut-out | Ø 80mm |
| Luminaire material | Aluminium |
| IP Rating | IP20/44 |

LED Specification

| | |
|---------------|-----------------------------------|
| LED | COB Luminus |
| Power | 8W |
| CRI | Ra90 |
| CCT | 2700K, 3000K, 3500K, 4000K, 5000K |
| Lumen | 560lm |
| Beam angle | 15°/24°/36°/50° |
| Drive current | DC200mA, 36V |
| Input voltage | AC220~240V/50-60Hz |
| Accessories | Honeycomb |

Ordering Information

| Beam angle | LED driver brand | LED CCT | Driver type | Power |
|--------------|------------------|---------|-----------------------|-------|
| 1 Narrow 15° | 1 Lifud | 1 2700K | 1 Triac Dimming | A 8W |
| 2 Medium 24° | 2 Tridonic | 2 3000K | 2 0-10V Dimming | |
| 3 Wide 36° | 3 Euchips | 3 4000K | 3 DALI Dimming | |
| 4 Flood 50° | | 4 5000K | 4 Regular Non-dimming | |